

Model ESC 100-280

File Number: EX28651

COMPANY

Alp Pompa (ETNA) Teknolojileri San. Ve Tic. A.S.
Dudullu OSB. 2.
Cad. No:14
Umraniye, Istanbul 34775 Turkiye

MODEL INFO

ESC 100-280 *refer to DS*
Centrifugal Fire Pumps, Split Case, Single Stage

RATING DETAILS

Rated Capacity, GPM (L/Min)	Inlet Size, in.	Outlet Size, in.	Minimum Net Pressure Range, psig (kPa)	Maximum Net Pressure Range, psig (kPa)	Approx Speed, RPM	Max Working Pressure, psig (kPa)
500 (1,892)	6	4	96 (661)	180 (1,241)	2980	296 (2,040)
750 (2,839)	6	4	91 (627)	176 (1,213)	2980	296 (2,040)
1,000 (3,785)	6	4	84 (579)	173 (1,192)	2980	296 (2,040)

Report Date: 2026-09-24
Revision Date: 2026-09-29

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Model ESC 125-320

File Number: EX28651

COMPANY

Alp Pompa (ETNA) Teknolojileri San. Ve Tic. A.S.
Dudullu OSB. 2.
Cad. No:14
Umraniye, Istanbul 34775 Turkiye

MODEL INFO

ESC 125-320 *ESC 125-320*
Centrifugal Fire Pumps, Split Case, Single Stage

RATING DETAILS

Rated Capacity, GPM (L/Min)	Inlet Size, in.	Outlet Size, in.	Minimum Net Pressure Range, psig (kPa)	Maximum Net Pressure Range, psig (kPa)	Approx Speed, RPM	Max Working Pressure, psig (kPa)
1,000 (3,785)	8	6	142 (979)	188 (1,296)	2980	310 (2,137)
1,250 (4,731)	8	6	141 (972)	187 (1,289)	2980	310 (2,137)
1,500 (5,677)	8	6	139 (958)	185 (1,275)	2980	310 (2,137)
2,000 (7,570)	8	6	132 (910)	181 (1,247)	2980	310 (2,137)

Report Date: 2026-09-24
Revision Date: 2026-09-29

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."